TECHNOSPACIO SWING GATE SERIES



Swing Turnstile

Model No:TS-S-500

Products Introduction:

The TS-S-500 Swing gates are stylish waist-high security speed gates that operate on the swing open principle with glass (or plastic) panels acting as the barrier gate. Depending on which side of the Technospacio Swing Lane the person approaches, the gate when authorised, will swing open in the opposing direction allowing them passage through the controlled lane. The Technospacio Swing Lane has the ability to embed most manufacturers access control readers beneath its top glass cover, and with the intuitive LED user indication and guidance, this security speed gate encompasses safety with high traffic flow capacity. The Technospacio Swing Lane is offered with different dimensions of swinging gates, which enables lane widths of up to 1000mm.

Application Location:

Using swing turnstiles is a popular choice for any sites where requires wide passage (for people carrying large parcels, or the disabled) strict pedestrian access control (anti-following) and fast accessing rate(at 40-45persons/minute), for example, station, hotels, banks, clubs, office buildings, gyms. They eliminate the need for attendants at entrances and provide a means to count the number of pedestrians entering into a facility. These turnstiles paired with card readers and electronic operation are the most popular choice for entrance and exit systems and can be found in most of them.

Access Control System (Optional)



SWIPE CARD

Accesswithauthorized cardandpaymentcard sex piece swipe to open the way



IRIS RECOGNITION

Use the authorized eyes of Iris Recognition to pass through the entry gates



FINGERPRINT RECOGNITION

Access with authorized fingerprint authentication



PALM VEIN RECOGNITION

Use authorized palm vein recognition to pass into



COIN/TICKET

Usedisposable coins to coin through to enter



FACE RECOGNITION

Use authorized face recognition to enter



URL: www.Technospacio.com

QR CODE

Scan in with authorization QR code and barcode



MANUAL OPERATION

Manualuse of wired andwireless to open gates for entry

Features



Reliability

Alloy steel swing hub prevents mechanical

Casework and swing arms manufactured in SUS304 stainless steel+paint

Electromagnets for lock are used only when being activated. They are in standby mode when the device is idle. Technospacio patented compact mechanism ensures the long life of the lubricating oil inside.

High quality electrical components



Safety and User-Orientated Design


- The arm designed for emergency purpose
- No exposed screws, safer for the user.
- ${\tt Smoothoperationdesigned formas}$ application
- The pictogram on the device indicatingaccesspermissionand direction of movement
- Specialdesigned cases hape, user-friendly for passenger to punch card or finger.
- Anti-tailgate


Easy Integration

- Flexible reader installation plate. Customerscaneasilyintegrate with third party redaer Standardelectricalinterface for third
- party device. By using compact mechanism, the turn stile has more space in side for
- Technospacioprovidesintegration serviceinfactory, with board and peripherals installed, ensuring compliance of the system. When the turnstile is delivered, just plug it in and do the setting. Save the cost of

Specifications

integration





Brand nam e	Tec hnos pac io
Motor type	DC brus hles s motor
Flow rate	40 - 50 pe o pl e/ m inut e
Passage width(mm)	≤1000
Rated Power	50W
Cabint material	SUS 304;1.5mm top lid/1.2mm side
Infared sensor	8 pairs
Input/Output signal	dry contact/relay signal
Dim ens ion	1508*160*1019mm
Net weight	55 KG
Gros s weight	57 KG
IP	IP 55
Operating Temperature	-10 °C- 60 °C
Operating Humidity	5%- 85%
Working Environment	Indoor/ Out door covered
Voic e prom pt	Yes

URL: www.Technospacio.com